


PRINTER GEN5®

GEN5™



FULLY COMPATIBLE

- Works with existing platforms, server-based & USB machines
- Compatible with GEN2U harnessing
- Can use PromoNet for promotional couponing

FASTER

- Faster CPU, faster print speed, faster customer connections

FLEXIBLE

- Prints TITO and promotional tickets

FUZION READY

- Potential for lottery ticket vending, race/ sports ticket vending, tax forms printing

OPERATIONALLY SOUND

- Intelligent ticket handling, dual channel communication, jam prevention technology, RS232, NetPlex, USB 2.0, GSA

THE NEW GEN5® PRINTER IS THE BETTER, SMARTER, FASTER WAY TO MAKE CONNECTIONS WITH CUSTOMERS



Watch our
Product Demo

With a lightning fast CPU, dual channel communication, intelligent ticket handling and cross-enterprise promotional couponing and superior electro-mechanical design, the GEN5 printer guarantees high reliability and easy maintenance with modern technology. Plus, the GEN5 is FUZION®-ready, and when combined with the iVIZION® bill validator, can open a wealth of potential new features.

GENERAL

Dimensions (WxDxH)

- 110mm x 304.8mm x 64.3mm

Weight

- 2.7 lbs.

Supply voltage

- 24Vdc @ 2.7A

Sensors

- Paper low, paper out, printer drawer open, ticket taken, ticket jam, black mark (includes a host controllable buzzer)

Printing speed

- 90mm/second (3.5"/second)

Print and present

- 2.2 seconds

Printing width

- 62mm (true near-edge printing)

Storage

- 300 tickets

Ticket tray extenders

- Interchangeable, 600, 900 ticket tray

Resolution

- 8 dots/mm (203 dpi)

Firmware

- Application in memory is reprogrammable (via Flash BIOS)

Self test

- Yes

Page mode

- Full page mode printing (simultaneous 4 orientation printing: 0°, 90°, 180°, 270°), line and box draw printer resident, bitmap graphics, printer resident (stored in Flash) graphics

Paper loading

- Manual

Paper feed

- Automatic

Media

- Direct thermal, top coated, fan folded and perforated

Paper specification

- 66mm W x 156mm L
4.5 mil, 1 color/2 colors

Bezel control

- Two high current ticket printing bezel control ports

User Interface

- 4 LED indicators, paper advance button

Upgrade port

- Allows for printer upgrades via USB download port or RS232C main port

CHARACTERISTICS

Printer languages

- TCL printer language (page description language) Subset of ESCP2

Fonts

- 8 (2.5 cpi, 3.3 cpi, 4.0 cpi, 5.5 cpi, 5.6 cpi, 7.3 cpi, 10.1 cpi, 20.5 cpi)

Font scalability

- May be independently scaled from 1x – 7x in both height and width

Barcodes

- PDF-417, Interleaved 2 of 5, Code 39, UPC-A, UPC-E, UPC-E+2, UPC-E-5, Codabar, EAN-13, EAN-8, Code 128, MSI, Data Matrix, QR Code

Memory

- Flash: 4MB
• RAM: 8MB

INTERFACE

Communications

- USB 2.0 game interface at 12Mbps, Separate USB download service port, Compliant with GSA GDS, IGT USB and traditional communication protocols RS232 and Netplex

ENVIRONMENTAL

Operating temperature

- 0°C to 65°C

Storage temperature

- -20°C to 75°C

Operating humidity

- 5 to 85% RH non-condensing

RELIABILITY

Print head life

- 93.2 miles (150km) 984,000 tickets based on US currency size

Maintenance

- Annual print head cleaning required

Certifications

- ISO 9001, CE certified, RoHS, UL

Ask your representative about all of our additional GEN5 options.



JCM Europe GmbH
Mundelheimer Weg 60
D-40472 Dusseldorf,
Germany
Tel: +49 211 530645-0

Japan Cash Machine Co., Ltd
N2-23-2, Higashi Nihonbashi,
Chuo-ku
Tokyo 103-0004, Japan
Tel: +81-3-5962-3731

JCM American Corporation
925 Pilot Road
Las Vegas, NV 89119, USA
Tel: +01 800-683-7248
(800# for USA, Canada & Mexico)
Tel: +01 702-651-0000

FOLLOW US ON



JCM Global, JCM Global logo, and other marks used herein are trademarks and registered trademarks of Japan Cash Machine Co., Ltd. and JCM American Corporation. Additional marks are registered trademarks of their respective owners. JCM Global reserves the right to change product specifications without notice.

Find out more at
www.jcmglobal.de

