SECURE. PRODUCTIVE. RECYCLING.





UBA®-RC RECYCLER

Reduce operational costs and keep customers happy with the amazing new UBA® RC from JCM Global®! UBA RC has two large-capacity chambers with Roller Friction Recycling Technology, holding recycled notes for instant payouts, keeping your equipment running and your customers happy. Plus, UBA RC has JCM's powerful anti-stringing technology, proven note acceptance and lockable removable cashbox.

FEATURES

- · Currency recycling
- · Two high-capacity recycling chambers
- · Roller Friction Recycling Technology
- · Accepts banknotes up to 85mm wide
- · Anti pull-back drum technology
- · Compact design
- · Field-proven UBA sensor package

BENEFITS

- · Reduces float & eliminates coin starvation
- · Recycle two denominations, up to 100 notes each
- Direct bulk note refill into recycling chamber for optimum uptime
- · Works for all global applications
- · Best protection against stringing
- · Optimum flexibility for device integration
- · Best counterfeit protection & first-time acceptance



CASHBOX

- · 400 notes
- · 1000 notes (optional)

BANKNOTE SIZE

- · Acceptance
 - · L: 120-170mm (4.72-6.69")
 - · W: 62-85mm (2.44-3.35") with 1000-note cash box
- · Recycler
 - · L: 120-158mm (4.72-6.22")
 - · W: 62-82mm (4.72-3.23")

RECYCLE BOX CAPACITY

· 100 notes x 2 denominations

POWER REQUIREMENTS

- DC + 24V (\pm 5%)
- · Standby 200mA
- · Operation 1.5A
- · Peak 2.5A

INTERFACE

- · Photocoupler Isolation
- · TTL
- · RS232C

ENVIRONMENT

• Operation: 5 to 50 °C (41 to 122 °F)

Storage: 20 to 60 °C (68 to 140 °F)

 Humidity: 30% - 85% RH (No Condensation)

BEZEL

- · Plastic Standard
- · Metal Optional



Removable lockable security cash box 400 notes



· Large recycling capacity in a

compact form



EMEA: 49.211.5306.4550 · JAPAN: 81.6.6703.8400 · US: 702.651.0000 · US: 800.683.7248

jcmglobal.com