

PORTABLE. FAST. SECURE.



BlueWave™ 2.0

Ride the wave of high-speed data transfer with the BlueWave 2.0 from JCM Global®. This amazing handheld tool is the perfect and easy way to load and upgrade your validator firmware right at the machine. Lightweight and powerful, the BlueWave 2.0 easily connects by USB or Serial interface and gets you up and running again in seconds.

FEATURES

- Load firmware at the machine
- LED indicators for battery charge state
- Operates on 2 AA size alkaline batteries
- Fast USB and Serial transfer
- Firmware storage and transfer via SD Cards
- USB connection for iVIZION®, TBV™, UBA® & Vega™; optional serial adapter for DBV-3x®, EBA 3x™, Taiko™ & WBA®

BENEFITS

- Quickly and easily updates your validator firmware
- Avoid inconvenient power failure
- Always ready, always working
- Quick & convenient for greater uptime
- Easily interchangeable SD cards for all protocols
- Easy standard connection for all JCM products



LOAD SPEED

- USB: 35-200 sec (depending on file size)
- Serial: 3-5 mins @ 38400 BAUD

INTERFACE

- USB 1.1 or 2.0
- RJ-45 to Serial adapter harness

PROGRAM MEMORY

- SD and SDHC Cards

DIMENSIONS (HxWxD)

- 177.79x85.09x31.75mm (7x3.35x1.25")

WEIGHT

- 226.8 grams (0.50 lbs.)

ENVIRONMENT

- Operation: 5 to 45 °C (41 to 113 °F)
- Operating Humidity: 30% to 80%
- Storage: -20 to 60 °C (-4 to 140 °F)
- Storage Humidity: 15% to 95% RH

POWER REQUIREMENTS

- 2 AA size alkaline batteries (3.0 V)

DESCRIPTION

ASSY, DT-200 BLUEWAVE

KIT, BLUEWAVE 2.0, iVIZION/UBA

KIT, BLUEWAVE 2.0, WBA

KIT, BLUEWAVE 2.0, PUB/TAIKO

KIT, BLUEWAVE 2.0, EBA-3X

KIT, BLUEWAVE 2.0, DBV-30X

HARN, BLUEWAVE WBA

HARN, BLUEWAVE PUB/TAIKO

HARN, BLUEWAVE EBA

CABLE, CAT5e, PATCH, 3', BLUE

CABLE, USB A/M TO B/M, 3', BLK

CABLE, USB A/M TO MINI B/M, 3', BLK



US: 702.651.0000 • US: 800.683.7248 • EU: 49.211.5306.4550 • JAPAN: 81.6.6703.8400

jcmglobal.com