

SECURE. FLEXIBLE. INNOVATIVE.



iPRO™

Introducing the all-new iPRO, the latest innovation from the world's currency transaction leader. iPRO is the secure and flexible way to increased profitability because it comes with one of the most sophisticated sensing and anti-stringing packages we have ever created. iPRO's modular design means it can quickly and easily replace an existing UBA® head for instant improved performance. One look, and you'll be ready to play like a pro.

FEATURES

- 100% compatible as UBA "plug-and-play" upgrade
- Sealed bill path for dust, liquid & light protection
- 7 Wavelength optical and magnetic sensors
- Dual exit sensors with anti-stringing drum device
- ICB® optional add-on
- Faster note-to-note speed
- Highest first time acceptance rate
- Down and Up Stacker

BENEFITS

- Cost-effective technology & anti-counterfeit upgrade
- Lowers cost of ownership & increases uptime
- Best counterfeit protection
- Best anti-stringing in the industry
- Dramatically improves accountability and drop process
- Increased profit potential and customer satisfaction
- Delivers better user experience
- One product for multiple OEM applications

ACCEPTANCE RATE

- 98% or greater

BANKNOTE SIZE

- Width: 62 - 85mm (2.44 - 3.35")
- Length: 120 - 170mm (4.73 - 6.69")

INSERTION DIRECTION

- Banknote: Four-way
- Barcode Coupon: Two-way faceup

ESCROW

- One note or one barcode coupon

CASH BOX CAPACITY

- 600 notes (standard)
- 1000 notes (optional)

DIMENSIONS (HxWxD)

- 298x114x234mm (11.73x4.49x9.21")

INTERFACE

- USB
- Photo-coupler isolation
- RS232C
- ccTalk

PROTOCOL

- ID-003 and OEM Serial, ccTalk

WEIGHT

- Unit and cash box: Approximately 4kg (8.81 lbs)

INSTALLATION

- Down Stack
- Up Stack

MEMORY

- 64 Mbit Flash memory standard

SUPPLY VOLTAGE

- 4.0A at 12V DC -5%, +15%
- 24V DC (Option)

CURRENT CONSUMPTION

- iPRO 100 (variable width model) 12V DC
- iPRO 101 (fixed width model) 12V DC

ENVIRONMENT

- Operation: +5°C to +50°C (41°F to 122°F)
- Storage: -20°C to +60°C (-4°F to 140°F)
- Operating: 30% to 85% RH (non-condensed)
- Storage Humidity: 30% to 85% RH (non-condensed)

APPROVALS

- CE/UL

OPTIONS

- ICB® (Intelligent Cash Box)
- Sentry® Bezel
- Metal® Bezel



AMERICAS: 1.702.651.0000 • AUSTRALASIA: 61.2.9648.0811 • EMEA: 49.211.5306.4550
JAPAN: 81.6.6703.8400 • MACAU: 853.2872.2684 • US: 1.800.683.7248

jcmglobal.com

JCM and JCM logo are registered trademarks of Japan Cash Machine Co., Ltd. and JCM American Corporation. All other marks are registered trademarks of their respective owners. JCM reserves the right to change product specifications without notice.