BILL VALIDATOR DBV®-400

DBV[®]-400







FAST ACCEPTANCE

Note-to-note speeds of less than 2 seconds

HIGH CAPACITY

Cashbox options of 300/500/1000 notes

EASY UPGRADE

Direct, easy replacement for the DBV-30x series

ROBUST DESIGN

Thick plastic frame and housing

FLEXIBLE APPLICATIONS

 Designed to work at -15° C to +60° C

FRAUD PROTECTION

 6 wavelengths of high-precision optical sensors, and optical and mechanical anti-stringing/ fishing sensors

JCM Global's DBV®-400 series has been meticulously developed based on our 25 years of experience in bill validation technology.



Watch our **Product Demo**

Highly secure and created for durability, the DBV-400 defeats cheats and keeps transactions and cash storage safe. The robust design is built with a thick plastic frame making it both long-lasting and lightweight. A choice of cash box options makes the DBV-400 the best solution for a wide range of automated payment applications. DBV-400 accepts banknotes up to 72mm wide.

State-of-the-art, high-precision sensor technology protects operators, and a banknote-to-banknote speed of less than 1.7 seconds keeps consumers happy. Its design keeps dust and liquid out, and a sleep mode provides minimal power consumption in idle status.



GENERAL SPECIFICATION



ACCEPTANCE RATE

• 98% +

BANKNOTE SIZE

• Width: 60-72mm • Length: 110-160mm

CAPACITY

• S: 300 notes • M: 500 notes 1000 notes

INTERFACES

- RS232C
- TTL
- Photo-coupler
- USB

PROTOCOLS

- ID-003 Serial
- ID-008 USB
- ID-044 Vend Serial
- ID-003 MDB
- ID-002 Pulsed

WEIGHT

- 1.3 kg (300 notes)
- 1.4 kg (500 notes)
- 1.6 kg (1,000 notes)

INSTALLATION

- Down Stack
- Up Stack

SUPPLY VOLTAGE

- 12-24VDC
- 12V, Max 1.9A
- 24V, Max 0.96A
- · Standby: 12VDC / 0.12A 24VDC / 0.07A
- Operation: 12VDC / 1.4A 234VDC / 0.7A
- Peak: 12VDC / 2.2A 24VDC / 1.6A

ENVIRONMENT

Operation: -15C to +60C

OPTIONS

· Bezel with illuminated logo









JCM Europe GmbH

Mundelheimer Weg 60 D-40472 Dusseldorf, Germany

Tel: +49 211 530645-0

JCM Global, JCM Global logo, and other marks used herein are trademarks and registered trademarks of Japan Cash Machine Co., Ltd. and JCM American Corporation. Additional marks are registered trademarks of their respective owners. JCM Global reserves the right to change product specifications without notice.

Japan Cash Machine Co., Ltd N2-23-2, Higashi Nihonbashi,

Chuo-ku Tokyo 103-0004, Japan

Tel: +81-3-5962-3731

JCM American Corporation 925 Pilot Road Las Vegas, NV 89119, USA

Tel: +01 800-683-7248 (800# for USA, Canada & Mexico Tel: +01 702-651-0000







