

# UBA<sup>®</sup> Pro

UNIVERSAL BILL ACCEPTOR



## IMPROVED DESIGN

- ▣ Longer life-cycle
- ▣ Dust and liquid resistant design

## BETTER PERFORMANCE

- ▣ Faster note-to-note speed and acceptance
- ▣ 2 or 4 way barcode reader
- ▣ Centering mechanism

## ENHANCED SECURITY

- ▣ Superior sensor package
- ▣ Best, patented anti-stringing technology
- ▣ Accepts the world's currencies

## GREATER SERVICEABILITY

- ▣ Service-friendly modular design to reduce service and repair downtime

**THE UBA<sup>®</sup> PRO** sets standards in automated transactions across the gaming, kiosk, and retail industries. Meticulously designed for modern business environments, the UBA Pro's improved design delivers better performance with a low cost of ownership.

The UBA Pro also supports the JCM FUZION<sup>®</sup> system. Once connected to FUZION, a suite of tools and features become available to help manage cash on the casino floor. These features include firmware download scheduling, cash box fullness monitoring, drop management, AML security monitoring, and a cashless wallet interface.

## GENERAL SPECIFICATIONS

### Acceptance Rate

98% or greater

### Banknote Size

- Centering Type (UBA-5x0 Series)
- Long side: 120 - 165mm (4.72 - 6.49in.)
  - Short side: 62 - 85mm (2.44 - 3.34in.)

### Banknote Insertion Direction

- Banknote: 4 ways  
Barcode Ticket: 2 ways (Face up)  
4 ways as option

### Dimensions (WxHxD)

301.1 (H) x 225 (D) x 114 (W)

### Weight Empty

Approx. 4kg (8.81lbs)  
(UBA Pro Unit + Frame + Standard 500 Note Cash Box)

### Supply Voltage

12V DC (-5%) - 24V DC (+5%)  
(Greater than 70W recommended)

### Validation Speed

- Centering Type (UBA-5x0 Series)
- 2.2 seconds or faster note to note speed

### Cash Box Type

- Security Box (Standard)  
ICB Box (Optional)

### Cash Box Capacity:

- 500 notes (new banknotes)  
900 notes (new banknotes)

### Compatibility:

Head unit of the UBA Pro functions with the existing frame, harnessing, voltages, interfaces, and cash boxes of the UBA<sup>®</sup>-10, -14, and -24.

### Interface

- USB (USB Specification Rev. 2.0 Compliance)  
(Full Speed/12Mbps)  
Photo-Coupler Isolation  
RS232C  
cc-Talk  
TTL

### Power Consumption

- 12.0V  
· Standby = 0.3A  
· Operation = 1.8A  
· Peak = 4.0A  
24.0V  
· Standby = 0.2A  
· Operation = 0.9A  
· Peak = 2.0A

### Environment

- Operating temperature: 5°C to +50°C (41°F to 122°F)  
Storage temperature: -20°C to +60°C (-4°F to 140°F)  
Humidity temperature: 15% to 85% RH (non-condensed)



Various Plastic Bezels



Various Metal Bezels



Cash Boxes

Contact your local JCM Territory Manager for more bezel options.